






OPTIFLEX

HIGH PRESSURE HYDRAULICS

BALFLEX 3-MAX

Bardzo wysokie ciśnienie, wąż wzmożniony potrójnym opłotem stalowym



Nr części	Ø nom.	dash size										
			mm	cal	mm	cal	MPa	PSI	MPa	PSI	mm	cal
10.1005.06	3/8"	- 6	9,5	0.38	17,7	0.70	50.0	7250	200.0	29000	180	7.09
10.1005.08	1/2"	- 8	12,7	0.50	20,5	0.81	47.0	6815	188.0	27260	230	9.06
10.1005.10	5/8"	- 10	16,0	0.63	24,4	0.96	41.0	5945	164.0	23780	250	9.84
10.1005.12	3/4"	- 12	19,0	0.75	27,8	1.09	37.5	5435	150.0	21750	300	11.81
10.1005.16	1"	- 16	24,4	1.00	34,7	1.37	31.5	4565	126.0	18270	340	13.39

**WYSOKIE CIŚNIENIE DLA LEŚNICTWA, PRZEZNACZONY DO MINERAŁÓW, OLEJÓW ROŚLINNYCH,
GLYCOLU, OLEJÓW NA BAZIE POLYGLYCOLU LUB ESTRÓW SYNTETYCZNYCH, OLEJÓW W EMULSJACH
WODY, WODY**

OPTIFLEX.PL

Adres: 32-440 Myślenice ul. Słowackiego 64 tel./fax 012 272 00 16 e-mail: optiflex@optiflex.pl , biuro@optiflex.pl
Oddział: 33-300 Nowy Sącz ul. Zdrojowa 32 tel./fax 018 441 09 e-mail: nowysacz@optiflex.pl